

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/CA04/002197

International filing date: 24 December 2004 (24.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US  
Number: 60/566,925  
Filing date: 03 May 2004 (03.05.2004)

Date of receipt at the International Bureau: 27 April 2005 (27.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

PA 1300686

# THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME;

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office


March 30, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/566,925

FILING DATE: May 03, 2004

PCT/CA04/02197



By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS

*L. Edelen*

L. EDELEN  
Certifying Officer

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**PROVISIONAL APPLICATION FOR PATENT COVER SHEET**

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. 22264 US PTO  
60/566925

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Helge		SEETZEN		Montreal, CANADA	
Additional inventors are being named on the _____ separately numbered sheets attached hereto					
<b>TITLE OF THE INVENTION (500 characters max)</b>					
Method for Efficient Computation of Image Frames for Dual-Modulation Display Systems Using Key Frames					
Direct all correspondence to: <b>CORRESPONDENCE ADDRESS</b>					
<input type="checkbox"/> Customer Number: <span style="border: 1px solid black; display: inline-block; width: 150px; height: 1.2em; vertical-align: middle;"></span>					
<b>OR</b>					
<input checked="" type="checkbox"/> Firm or Individual Name		The University of British Columbia - Industry Liaison Office			
Address		#103 -6190 Agronomy Road			
Address					
City	Vancouver	State	BC	Zip	V6T 1Z3
Country	CANADA	Telephone	6048228594	Fax	6048225998
<b>ENCLOSED APPLICATION PARTS (check all that apply)</b>					
<input checked="" type="checkbox"/> Specification Number of Pages <u>3</u>		<input type="checkbox"/> CD(s), Number _____			
<input type="checkbox"/> Drawing(s) Number of Sheets _____		<input type="checkbox"/> Other (specify) _____			
<input type="checkbox"/> Application Date Sheet. See 37 CFR 1.76					
<b>METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT</b>					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				<div style="border: 1px solid black; padding: 10px; width: 100px; margin: 0 auto;">FILING FEE Amount (\$)  80.00</div>	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees.					
<input type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: _____					
<input checked="" type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

[Page 1 of 2]

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME ANNARI FAURIETELEPHONE 604-822-8594Date 30 April 2004

REGISTRATION NO. \_\_\_\_\_

(if appropriate)

Docket Number: UBC 04-124**USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT**

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

## THE UNIVERSITY OF BRITISH COLUMBIA

April 30, 2004

Hon. Commissioner for Patents  
2011 South Clark Place  
Crystal Plaza Two, Lobby, Rm 1B03  
Arlington, Virginia 22202

Dear Sir:

Re: Provisional Patent Application for "Method for Efficient Computation of  
Image Frames for Dual-Modulation Display Systems Using Key Frames"  
UBC file no: 04-124

Enclosed please find the necessary documents for filing a Provisional Patent  
Application for the above-identified technology on behalf of The University of British  
Columbia. Also enclosed is Credit Card payment form PTO-2038 to cover the cost  
of the \$80.00 application fee.

Thank you,

Sincerely,



Annari Faurie  
*Patent Manager*

Encl.



U-I-L-O

UNIVERSITY-INDUSTRY  
LIAISON OFFICE

#103 - 6190 Agronomy Road  
Vancouver, BC  
V6T 1Z3

Tel: (604) 822-8580  
Fax: (604) 822-8589  
Web: [www.uilo.ubc.ca](http://www.uilo.ubc.ca)

**TO: Mail Stop Provisional Patent Application**  
US Patent and Trademark Office  
2011 South Clark Place  
Crystal Plaza Two, Lobby, Rm 1B03  
Arlington, Virginia 22202

**Enclosures:**

1. Provisional application for patent cover sheet
2. Specifications, 3 pages
3. Credit card payment form PTO-2038 for \$80.00 filing fee

## Method for Efficient Computation of Image Frames for Dual-Modulation Display Systems Using Key Frames

### Real time Video Computation for High Dynamic Range Displays

A dual modulation high dynamic range (HDR) display (see US patent application serial number 10/469,473, incorporated herein by reference) uses two image modulators in series. Three key implementations have been designed so far: A controlled array of light emitting diodes (LED) or other light sources projecting light through a liquid crystal display (LCD), a bright backlight projecting light through two LCDs in series, and a video projector projecting light through an LCD. In order to avoid alignment artifacts between the two modulators each design uses a varying degree of resolution mismatch between the two modulators where the front LCD is high resolution colour and the rear modulators (LED, first LCD, projector respectively) is low resolution. The front image is modified to correct for the blur of the rear image such that the combined output image is a high resolution HDR image. In the following we describe the first (LED based) design for the discussion but the method applies to all HDR display designs with a resolution mismatch between the modulators.

One of the drawbacks of this system is that the rendering (computation on the graphic card) of the image couplet is very computationally expensive. In principle, images are rendered in the following way:

1. A floating point or higher than 8-bit image ("input image") is provided to the algorithm
2. Appropriate intensities for each LED are established. The corresponding driving levels are stored ("LED Values").
3. The effective luminance distribution from the entire LED array is calculated by adding the modulated point spread functions (PSF) of the LEDs together. This is very costly as each image pixel has to be rendered multiple times to account for light coming from all LEDs with a PSF that stretches onto that pixel.
4. The input image is divided by the effective luminance distribution to yield the LCD image.
5. Both LCD image and LED values are sent to the display
6. At the display the LED array is modulated by the incoming LED values to create the effective luminance distribution which is then optically modulated by the transmission of the LCD according to the LCD image. The final image output corresponds to the input image.
7. This process is repeated for the next image frame.

This invention describes a method to reduce the computation time associated with the third step, which is the most costly. Instead of following the above procedure for each frame of the image we can assume that from one frame to the next there are only small changes to the image. As a result it is possible to calculate a single LED image (LED values and the associated effective luminance distribution) and then use it for one or more additional frames. The LCD image will be continually modified to make the necessary changes from frame to frame but this is computationally much less costly. By using an LED key frame every third frame the computation cost would be approximately 1/3 of the cost associated with frame by frame computation and the procedure would look like this:

1. calculate LED key frame
2. divide first frame by LED key frame to get first LCD image
3. display LED key frame and first LCD image
4. divide second frame by LED key frame to get second LCD image
5. display LED key frame and second LCD image
6. divide third frame by LED key frame to get third LCD image

7. display LED key frame and third LCD image
8. calculate second LED key frame
9. divide fourth frame by second LED key frame to get fourth LCD image
10. display second LED key frame and fourth LCD image
11. etc

As will be obvious to one skilled in the art, very simple modifications to this procedure will enable the use of LED key frame changes every second, fourth, fifth ... nth, frame.

The frames between key frames will be very accurate as long as the luminance changes during a key frame sequence are minor and can be contained within the dynamic range of the LCD alone (200:1 for a standard LCD which is significantly higher than most frame-to-frame luminance changes). The only artifacts introduced by this method occur if in a particular key frame the LCD dynamic range is already used to the maximum to correct for a high contrast boundary in the image and that boundary becomes even higher contrast in a subsequent non-key frame. These situations are very rare and are unlikely to be visible at video rates.

These artifacts can be further reduced by a dynamic use of the key frames. Instead of fixing their occurrence to once every few frames it is possible to establish one key frame and then keep count of the number of pixel per new frame which are not accurately reproducibly just by modifying the LCD image. If a certain threshold is exceeded the software renders a new key frame and otherwise no changes are necessary. Since the process of dividing the new frame by the LED key frame is very fast (linear process of one division operation per pixel) this could happen without any major delay. If the number of artifact pixels is higher than the threshold then the software calculates and uses a new LED key frame. If not, then the calculations for this frame are done (the division has already yielded the LCD image in addition to the number of artifact pixel). Such a dynamic key frame structure could dramatically reduce computation time for some applications where for long periods no major luminance changes occur in a scene.

If a key frame needs to be computed then the resulting lag can be distributed over several frames. In the interim period between the failure of the old key frame and the finished calculation of the new key frame it is possible to use different approximation of the accurate key frame. Any choice of combination from the list of options is appropriate:

- The interim frames can use a standard key frame. A standard key frame would be an approximately appropriate pattern that has been pre-computed. The system can rapidly execute a search through a list of pre-computed pattern to determine which is most suitable for the interim period. Examples of common pre-computed key frames are
  - all LEDs on at mid level
  - all LEDs full on
  - half or quarter of the LEDs full on
  - half or quarter of the LEDs half on
  - all previously computed key frames
- It is also possible to compute an interim key frame rapidly by relaxing the accuracy requirements of the LED point spread simulation (i.e. simulating the actual light distribution per LED with an approximate Gaussian, etc). This method will reduce the lag between key frame computations and the introduced imperfections are unlikely to be visible to the viewer as the result will be approximately accurate and perfect accuracy will be reached very rapidly once the new key frame is available. The accuracy of this approximation can be increased at each frame until the next perfect key frame has been established
- Since the pixels that cannot be reproduced with the old key frame are known it is possible to replace just the LED values corresponding to those pixels. Since the LED values of the old key frame are known it is possible to locate the inappropriate LED, subtract its point spread function multiplied by the corresponding LED value in the old key frame from the old key

frame. This effectively provides the LED luminance pattern under the old key frame setting with the inappropriate LED missing. The next step is to establish the appropriate LED value by the usual method. This new value multiplied by the point spread function of the LED can then be added to the modified key frame. This process is repeated as often as necessary until all inappropriate LED values have been replaced. The key frame is now appropriate for the image again. This update can take several frames and should proceed in the order of greatest error (i.e. the first LED to be replaced is the one with the largest number of pixels that cannot achieve the required value with the old key frame.)